

## TECHNICAL SHEET

### PRODUCT: Metallic putty DURCO BO

#### Description:

Poliester metallic putty. Repair all kind of defects in iron and steel castings. Easy to apply and grind/sand-papering.

Good resistance/adherence and strenghtness. Quick curing time.

#### Characteristics:

- Easy application
- Can be apply in every kind of iron and steel castings
- Short curing time: 25 minutes
- Can be painted over
- No machinable

#### Physical Properties: (20°C)

Type of product	Metalic poliester mastic
physical aspect	Paste
Colour	metalic grey
Viscosity	Paste
Curing time	30 minutes at 20°C
Streghtness	127HB
Contraction after cured	No contraction
Paste / Hardener percentage	30: 1
Pot Life at 20°C	20 minutes
Reapplication time	5-20 minutes
Density	1768 at 20/4°C
Specifc volume	1,90 grm/cc at 20C°
Maxim temperature	120°C
Steam preasure	3,1 Kpc at 50°C
Optimal temperature for application	Min 5 - max 40C°
Corrosovity	No corrosive for metals
Test done	
Strenghtness measure with a digital Proceq HB (AC2)	

## TECHNICAL SHEET

### Application:

**Clean** the surface to be repaired

Use Peroxid of Benzoilo as hardener:

Temperature vs % of hardener

Application Temperature	% of hardener
<10 C°	3 – 3,5%
10- 20 C°	2– 2,5 %
>20 C°	1,5 – 2%

**IMPORTANT:** Take out from the can the quantity you want to apply. Mix properly the paste and hardener during 5-10 seconds

Once mixed, **Apply** the mastic, better with a spatula in a way that the mixture can be smoothly adhered to the surface to repair. Repeat it if necessary.

Leave cure during 25 or 30 minutes. Can be manually sandpapered (P120-180-240) and edges (P320).

**Painted:** Once cured and sandpapered/grinded, clean the surface before painted.

### Shelf life (temperature 5-40°C):

12 months

Please, read the MSDS of the product before use it.

### INDUSTRIAL APPLICATION ONLY