

## TECHNICAL SHEET

### PRODUCT: REFRACTORY MASTIC R 70

#### Description:

Mineral base, solvent free, ready to use. It cures through the evaporation of the water that contains, becoming a hard and consistent mass, resistant to high temperatures and fire. Good adhesion on iron, concrete and refractory bricks.

#### Applications:

It is suitable for sealing all facilities, conductions or machines that are subjected constantly to high temperatures like kitchens, fire places, chimneys, stoves, smoke pipes, etc.

#### Characteristics:

<b>Density</b>	1,96 g/nl
<b>Colour</b>	Black
<b>Application temperature</b>	-10 +35°C
<b>Temperature Resistance</b>	Up to 1500°C
<b>Flame Resistance</b>	Excellent
<b>Water Resistance</b>	No

#### Use:

Cut the conical tip of the cartridge, screw on the nozzle and cut to required size. Insert the cartridge to the applicator gun and extrude the sealant forming a continuous strand and avoiding to form air pockets. We recommend the use of a pneumatic applicator gun. Not suitable for outdoor applications or those ones that could be exposed to water condensations.

Dry off completely before the action of the flames or of high temperatures.

The surfaces to seal should be firm, consistent, clean and totally dry.

#### Packing and Storage:

In 300 ml cartridges (25 cartridges / carton)

In dry and cool places, at temperature between +5 and +35°C

## TECHNICAL SHEET

**Shelf life:**

12 months.

During the curing process, avoid the contact with the mucous (eyes, mouth, etc.) and wash the hands after use.